

Material Safety Data Sheet

B-9 Chem-Dip Carburetor and Parts Cleaner

MSDS No. 014

Date of Preparation: 10-29-99

Revision: 4-21-06

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: B-9 Chem-Dip Carburetor and Parts Cleaner

Part Number(s): 0901, 0905 (Blend 2AAD)

AS OF 4/24/2006, DATE CODE 11406, PART NUMBER 0996 NO LONGER CONTAINS THIS MATERIAL COMPOSITION. SEE MSDS # 076 FOR PART NUMBER 0996 PACKAGED ON OR AFTER 4/24/2006.

CAS Number: Not applicable to mixtures

General Use: Automotive product

Manufacturer: Berryman Products, Inc., 3800 E. Randol Mill Rd., Arlington, TX 76011-5434

Phone: 1-800-433-1704, Emergency phone number: 1-800-535-5053.

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt or % vol
Methylene Chloride (Dichloromethane)	75-09-2	55-65
Cresols	Mixture	10-15
Mixed Xylenes	1330-20-7	20-30
Sodium Bichromate	10588-01-9	<4
Ethyl Benzene	100-41-4	<6

Trace Impurities:

Ingredient	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Methylene Chloride (Dichloromethane)	125	none estab.	50	none estab.	none estab.	none estab.	none estab.
Cresols	5	none estab.	5	none estab.	none estab.	none estab.	none estab.
Mixed Xylenes	100	none estab.	100	150	none estab.	none estab.	none estab.
Sodium Bichromate	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.	none estab.
Ethyl Benzene	100	none estab.	100	125	none estab.	none estab.	none estab.

Section 3 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Clear, Light Brown, Antiseptic

Vapor Pressure: 350 mm Hg at 68 °F (Major component)

Vapor Density (Air=1): Heavier than air

Density: 9.43 lbs/gal

Specific Gravity (H₂O=1, at 4 °C): 1.130

Boiling Point: 104-324 °F

Refractive Index: 1.4649

% Volatile: 85

Evaporation Rate: Slower than ether

Section 4 - Fire-Fighting Measures

Flash Point: 210 °F


Flash Point Method: CC

LEL: 13% v/v (Major component)

Flammability Classification: Class IIIB

Extinguishing Media: Carbon dioxide, foam, dry chemicals.

NFPA



Unusual Fire or Explosion Hazards: Combustible liquid. Vapors can cause flash fire. Toxic. Poison. Corrosive.

Fire-Fighting Instructions: Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Wear self-contained breathing apparatus pressure demand, MSNA/OSHA (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

Section 5 - Stability and Reactivity

Stability: B-9 Chem-Dip Carburetor and Parts Cleaner is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities & Conditions to Avoid: Isolate from oxidizers, heat, sparks, electric equipment and open flame. May be corrosive to aluminum, magnesium, titanium and their alloys.

Hazardous Decomposition Products: Thermal oxidative decomposition of B-9 Chem-Dip Carburetor and Parts Cleaner can produce carbon monoxide, carbon dioxide, chlorine containing gases and hydrogen chloride.

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Skin, dermal, inhalation and ingestion.

Target Organs: Eyes, skin, respiratory system, CNS, liver and kidneys.

Acute Effects: May cause irritation to the eyes, skin, nose, throat and respiratory system. Nausea, headache, light-headedness, dizziness, and dermatitis. Burns and severe corneal damage may occur if direct contact with skin and eyes. Harmful or fatal if swallowed.

Carcinogenicity: IARC, NTP, and OSHA list Hexavalent Chromium as a carcinogen.

Chronic Effects: May affect liver, kidneys or central nervous system. Can cause nervous system depression. Potential cancer hazard.

Emergency and First Aid Procedures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. Get medical attention immediately.

Eye Contact: Immediately flush eyes with plenty of water. Get medical attention, IMMEDIATELY.

Skin Contact: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

Ingestion: GET MEDICAL ATTENTION IMMEDIATELY. Do not induce vomiting.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Eliminate all sources of ignition. Stop spill at source. Wear appropriate personal protective equipment (Sec. 8). Contain the spill to facilitate cleanup with absorbent. Use non-sparking tools and equipment. Transfer to disposal containers.

Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state and local regulations.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 8 - Exposure Controls / Personal Protection

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA.

Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling Precautions: Avoid prolonged breathing of vapor and contact with eyes, skin and clothing. Use in well ventilated area. Wash thoroughly after handling.

Storage Requirements: Keep away from heat, sparks and flame. Keep container closed when not in use. Keep away from food.

California Proposition 65: This product contains the following chemicals know to the state of California to cause cancer and/or reproductive toxicity: Hexavalent Chromium and Dichloromethane (Methylene Chloride).

DOT Transportation Data (49 CFR 172.101):

Part Number(s): 0901, 0996

Shipping Name: Consumer
Commodity

Hazard Class: ORM-D

ID No.: N/A

Packing Group: N/A

Part Number(s): 0902, 0905

Shipping Name: Toxic Liquids
Organic, N.O.S., contains
(Chlorinated Hydrocarbons)

Hazard Class: 6.1

ID No.: UN 2810

Packing Group: III

SARA Title III Section 313 Supplier Notification:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the emergency Planning & Community Right-To-Know-Act of 1986 & of 40CFR 372: Methylene chloride, m-Cresol (CAS #108-39-4), Mixed Xylenes, p-Cresol (CAS # 106-44-5), Hexavalent Chromium (CAS # 7440-47-3), and Ethyl Benzene.

Prepared By: Alicia L. Reed

Disclaimer: All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product. Users also assume all risks in regards to the publications of use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.