



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

SECTION 1. IDENTIFICATION

Product name : MaxLife™ DEX/MERC ATF
Automatic Transmission Fluid

Product code : 786953

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone : +1-800-VALVOLINE (+1-800-825-8654)
number

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 50 - < 60



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Distillates (Fischer-Tropsch), heavy, C18-50-branched, cyclic and linear	848301-69-9	>= 30 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 1.5 - < 5
LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED	72623-86-0	>= 1.5 - < 5
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 1 - < 1.5
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 1 - < 1.5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures. Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: carbon dioxide and carbon monoxide
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.
- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	ACGIH



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

		(Inhalable particulate matter)		
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.
No personal respiratory protective equipment normally required.

Hand protection
Material : neoprene, nitrile rubber
Break through time : >= 240 min
Glove thickness : >= 0.35 mm
Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.

Eye protection : Safety glasses
Skin and body protection : Protective suit
Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : red



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Odour	:	mild
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	> 424 °F / 218 °C (1013 hPa)
Flash point	:	394 - 480 °F / 201 - 249 °C Method: Cleveland open cup
Evaporation rate	:	< 1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	1 hPa Calculated Vapor Pressure
Relative vapour density	:	> 1 AIR=1
Relative density	:	No data available
Density	:	0.837 g/cm ³ (60.01 °F / 15.56 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	28.8 mm ² /s (104 °F / 40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Remarks: No mortality observed at this dose.

distillates (petroleum), hydrotreated light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified due to lack of data.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Species : Rabbit
Result : No skin irritation

distillates (petroleum), hydrotreated light paraffinic:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Product:

Result : Slight, transient irritation
Remarks : Expected based on components.



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Species : Rabbit
Result : No eye irritation

distillates (petroleum), hydrotreated light paraffinic:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

distillates (petroleum), hydrotreated light paraffinic:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), hydrotreated light paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

distillates (petroleum), hydrotreated light paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Distillates (Fischer-Tropsch), heavy, C18-50-branched, cyclic and linear:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated light paraffinic:

May be fatal if swallowed and enters airways.

distillates (petroleum), hydrotreated light paraffinic:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (Fischer-Tropsch), heavy, C18-50-branched, cyclic and linear:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), hydrotreated light paraffinic:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

distillates (petroleum), hydrotreated light paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

distillates (petroleum), hydrotreated light paraffinic:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-
octanol/water : log Pow: Expected > 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological
information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

Distillates (petroleum), hydrotreated light paraffinic 64742-55-8
distillates (petroleum), hydrotreated light paraffinic 64742-55-8

Pennsylvania Right To Know

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7
Distillates (Fischer-Tropsch), heavy, C18-50-branched, cyclic and linear 848301-69-9
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7
LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED 72623-86-0
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8
distillates (petroleum), hydrotreated light paraffinic 64742-55-8

Maine Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

Vermont Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

Washington Chemicals of High Concern

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

California List of Hazardous Substances

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8
distillates (petroleum), hydrotreated light paraffinic 64742-55-8

California Permissible Exposure Limits for Chemical Contaminants

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory
TSCA : All substances listed as active on the TSCA inventory
AIIC : Not in compliance with the inventory
DSL : All components of this product are on the Canadian DSL
ENCS : Not in compliance with the inventory



SAFETY DATA SHEET
 MaxLife™ DEX/MERC ATF Automatic
 Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
 02/28/2024

- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- NZIoC : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


Inventories

AllC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1
Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
OSHA Z-1 / TWA : 8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/30/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



Valvoline™
Global

SAFETY DATA SHEET
MaxLife™ DEX/MERC ATF Automatic
Transmission Fluid

Version: 5.0

Revision Date: 01/30/2024

Print Date:
02/28/2024

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0367943