



1. Chemical product and company identification

Product name Castrol GTX High Mileage 10W-30
MSDS # 463541
Code 463541-US12, US13, CA01
Product use Engine oils.
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer BP Lubricants USA Inc.
 1500 Valley Road
 Wayne, NJ 07470
 Telephone: (973) 633-2200
 Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
 Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION 1 (866) 4 BP - MSDS
 (866-427-6737 Toll Free - North America)
 email: bpcares@bp.com

2. Composition/information on ingredients

| Ingredient name | CAS # | % |
|---------------------------|------------|---------|
| Base oil - highly refined | Mixture | 85 - 90 |
| Base oil - highly refined | 64742-55-8 | 1 - 5 |
| Base oil - highly refined | 64742-54-7 | 10 - 15 |

3. Hazards identification

Physical state Liquid.
Color Clear. Amber.
Emergency overview WARNING!
 CAUSES SKIN IRRITATION.
 MAY CAUSE EYE IRRITATION.
 MAY CAUSE RESPIRATORY TRACT IRRITATION.
 Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects
Eyes May cause eye irritation.
Skin Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Used engine oil may contain hazardous components which have the potential to cause skin cancer.
Inhalation May cause respiratory tract irritation.

| | | | | | |
|--------------|---------------------------------|---------------|-------------------------|----------|-------------|
| Product name | Castrol GTX High Mileage 10W-30 | Product code | 463541-US12, US13, CA01 | Page: | 1/6 |
| Version | 1 | Date of issue | 05/01/2007. | Format | US |
| | | | | Language | ENGLISH. |
| | | | Build 5.3.1 | | (ENGLISH) |

| | |
|--|---|
| Ingestion | Ingestion may cause gastrointestinal irritation and diarrhea. |
| Medical conditions aggravated by over-exposure | None identified. |
| See toxicological information (section 11). | |

4. First aid measures

| | |
|--------------|--|
| Eye contact | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention. Get medical attention if irritation occurs. |
| Skin contact | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Ingestion | Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of this material are swallowed, call a physician immediately. |

5. Fire-fighting measures

| | |
|--------------------------------------|---|
| Flammability of the product | May be combustible at high temperature. |
| Products of combustion | carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.) sulfur oxides (SO ₂ , SO ₃ etc.) phosphorus oxides metal oxide/oxides |
| Unusual fire/explosion hazards | Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. |
| Fire-fighting media and instructions | In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet. |
| Protective clothing (fire) | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions | Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures"). |
| Environmental precautions and clean-up methods | If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information. |
| Personal protection in case of a large spill | Chemical splash goggles. Chemical resistant protective suit. Boots. Chemical resistant gloves. Vapor respirator or a self-contained breathing apparatus. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator. |

| | | | | |
|--------------|---------------------------------|---------------|-------------------------|-------------|
| Product name | Castrol GTX High Mileage 10W-30 | Product code | 463541-US12, US13, CA01 | Page: 2/6 |
| Version | 1 | Date of issue | 05/01/2007. | Format |
| | | | | US |
| | | | | Language |
| | | | | ENGLISH. |
| | | | | (ENGLISH) |
| | | | | Build 5.3.1 |

7. Handling and storage

| | |
|----------|--|
| Handling | Avoid contact with skin and clothing. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling. |
| Storage | Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. |

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Occupational exposure limits

Base oil - highly refined

ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

ACGIH (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Some states may enforce more stringent exposure limits.

Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes

Avoid contact with eyes. Chemical splash goggles.

Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

Wear gloves that cannot be penetrated by chemicals or oil.

Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

| | |
|--------------------|--|
| Physical state | Liquid. |
| Color | Clear. Amber. |
| Heat of combustion | Not available. |
| Pour Point | -35 °C |
| Specific gravity | 0.869 |
| Solubility | insoluble in water. |
| Viscosity | Kinematic: 11.7 to 12.3 mm ² /s (11.7 to 12.3 cSt) at 100°C |

10. Stability and reactivity

| | |
|---|---|
| Stability and reactivity | The product is stable. |
| Conditions to avoid | Keep away from heat, sparks and flame. |
| Incompatibility with various substances | Reactive or incompatible with the following materials: oxidizing materials. |
| Hazardous decomposition products | carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.) sulfur oxides (SO ₂ , SO ₃ etc.) phosphorus oxides metal oxide/oxides |
| Hazardous polymerization | Will not occur. |

11. Toxicological information

| | |
|----------------------|---|
| Acute toxicity | USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained. |
| Chronic toxicity | |
| Carcinogenic effects | No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA). |
| Mutagenic effects | No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen. |
| Reproductive effects | No component of this product at levels greater than or equal to 0.1% is classified by established regulatory criteria as a reproductive toxin. |
| Teratogenic effects | No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic. |

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

| | | | | | |
|--------------|---------------------------------|---------------|-------------------------|----------|-------------|
| Product name | Castrol GTX High Mileage 10W-30 | Product code | 463541-US12, US13, CA01 | Page: | 4/6 |
| Version | 1 | Date of issue | 05/01/2007. | Format | US |
| | | | | Language | ENGLISH. |
| | | | Build 5.3.1 | | (ENGLISH) |

13. Disposal considerations

Waste information Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/MDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 12(b) one-time export notification:: Diphenylamine
TSCA 12(b) annual export notification: lead

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol GTX High Mileage 10W-30: Immediate (Acute) Health Hazard

SARA 313

Form R - Reporting requirements This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Zinc alkyl dithiophosphate; Arsenic: 1 lbs. (0.4536 kg); Cadmium: 10 lbs. (4.536 kg); lead: 10 lbs. (4.536 kg);

State regulations

Massachusetts Substances **Massachusetts RTK:** The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

New Jersey Hazardous Substances **New Jersey Hazardous Substances:** None of the components are listed.

Pennsylvania RTK Hazardous Substances **Pennsylvania RTK:** None of the components are listed.

WARNING: This product contains a chemical known to the State of California to cause cancer. Paraffin oils, ; Arsenic

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Cadmium; lead

Inventories

Canada inventory: All components are listed or exempted.

Europe inventory: At least one component is not listed in EINECS but all such components are listed in ELINCS.
Please contact your supplier for information on the inventory status of this material.

Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory (ENCS): At least one component is not listed.

Korea inventory (KECI): All components are listed or exempted.

Philippines inventory (PICCS): At least one component is not listed.

Product name Castrol GTX High Mileage 10W-30

Product code 463541-US12, US13, CA01

Page: 5/6

Version 1 Date of issue 05/01/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

16. Other information

Label requirements

WARNING!

CAUSES SKIN IRRITATION.
MAY CAUSE EYE IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health - 1
Flammability 1
Physical Hazard 0
Personal protection X

National Fire
Protection
Association
(U.S.A.)



History

Date of issue

05/01/2007.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name Castrol GTX High Mileage 10W-30

Product code 463541-US12, US13, CA01

Page: 6/6

Version 1

Date of issue 05/01/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)