



## 1. Chemical product and company identification

**Product name** Castrol GTX High Mileage 10W-40  
**MSDS #** 463542  
**Code** 463542-US12, US13  
**Product use** Engine oils.  
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.  
**Manufacturer** BP Lubricants USA Inc.  
 1500 Valley Road  
 Wayne, NJ 07470  
 Telephone: (973) 633-2200  
 Telecopier: (973) 633-7475  
**EMERGENCY HEALTH INFORMATION:** 1 (800) 447-8735  
 Outside the US: +1 703-527-3887 (CHEMTREC)  
**EMERGENCY SPILL INFORMATION:** 1 (800) 424-9300 CHEMTREC (USA)  
**OTHER PRODUCT INFORMATION** 1 (866) 4 BP - MSDS  
 (866-427-6737 Toll Free - North America)  
 email: bpcares@bp.com

## 2. Composition/information on ingredients

Ingredient name	CAS #	%
Base oil - highly refined	Mixture	80 - 85
Base oil - highly refined	64742-54-7	10 - 15
Base oil - highly refined	64742-55-8	1 - 5
Zinc alkyl dithiophosphate	68649-42-3	1 - 5

## 3. Hazards identification

**Physical state** Liquid.  
**Color** Clear. Amber.  
**Emergency overview** WARNING!  
 CAUSES SKIN IRRITATION.  
 MAY CAUSE EYE IRRITATION.  
 MAY CAUSE RESPIRATORY TRACT IRRITATION.  
 Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.  
**Routes of entry** Dermal contact. Eye contact. Inhalation. Ingestion.  
**Potential health effects**  
**Eyes** May cause eye irritation.  
**Skin** Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Used engine oil may contain hazardous components which have the potential to cause skin cancer.

Inhalation	May cause respiratory tract irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.
Medical conditions aggravated by over-exposure	None identified.

See toxicological information (section 11).

## 4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of this material are swallowed, call a physician immediately.

## 5. Fire-fighting measures

Flammability of the product	May be combustible at high temperature.
Products of combustion	carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO <sub>2</sub> etc.) phosphorus oxides metal oxide/oxides
Unusual fire/explosion hazards	Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
Fire-fighting media and instructions	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.
Protective clothing (fire)	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## 6. Accidental release measures

Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Environmental precautions and clean-up methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Chemical splash goggles. Chemical resistant protective suit. Boots. Chemical resistant gloves. Vapor respirator or a self-contained breathing apparatus. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

Product name	Castrol GTX High Mileage 10W-40	Product code	463542-US12, US13	Page: 2/6
Version	1	Date of issue	05/08/2007.	Format
				US
				Language
				ENGLISH.
				( ENGLISH )
				Build 5.3.1

## 7. Handling and storage

Handling	Avoid contact with skin and clothing. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

#### Occupational exposure limits

Base oil - highly refined

**ACGIH (United States).**  
STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral  
**OSHA (United States).**  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

**ACGIH (United States).**  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral  
STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral  
**OSHA (United States).**  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

**ACGIH (United States).**  
STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral  
**OSHA (United States).**  
TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Zinc alkyl dithiophosphate

None assigned.

Some states may enforce more stringent exposure limits.

#### Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

#### Personal protection

##### Eyes

Avoid contact with eyes. Chemical splash goggles.

##### Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

##### Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

##### Hands

Wear gloves that cannot be penetrated by chemicals or oil.

Recommended: Nitrile gloves.

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

Product name	Castrol GTX High Mileage 10W-40	Product code	463542-US12, US13	Page:	3/6
Version	1	Date of issue	05/08/2007.	Format	US
				Language	ENGLISH.
			Build	5.3.1	( ENGLISH )

---

## 9. Physical and chemical properties

Physical state	Liquid.
Color	Clear. Amber.
Heat of combustion	Not available.
Pour Point	-36 to -33 °C
Specific gravity	0.871 to 0.877
Solubility	insoluble in water.
Viscosity	Kinematic: 15.5 to 16 mm <sup>2</sup> /s (15.5 to 16 cSt) at 100°C

---

## 10. Stability and reactivity

Stability and reactivity	The product is stable.
Conditions to avoid	Keep away from heat, sparks and flame.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO <sub>2</sub> etc.) sulfur oxides (SO <sub>2</sub> , SO <sub>3</sub> etc.) phosphorus oxides metal oxide/oxides
Hazardous polymerization	Will not occur.

---

## 11. Toxicological information

Acute toxicity	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Chronic toxicity	
Carcinogenic effects	No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).
Mutagenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.
Reproductive effects	No component of this product at levels greater than or equal to 0.1% is classified by established regulatory criteria as a reproductive toxin.
Teratogenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

---

## 12. Ecological information

### Ecotoxicity

No testing has been performed by the manufacturer.

Product name	Castrol GTX High Mileage 10W-40	Product code	463542-US12, US13	Page:	4/6	
Version	1	Date of issue	05/08/2007.	Format	US	
			Build	5.3.1	Language	ENGLISH.
					( ENGLISH )	

## 13. Disposal considerations

### Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/MDG, IATA/ICAO)

## 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b):** All components are listed or exempted.

TSCA 12(b) one-time export notification:: Diphenylamine

TSCA 12(b) annual export notification: lead; Alkylated phenol (P-00-346)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:** Castrol GTX High Mileage 10W-40: Immediate (Acute) Health Hazard

### SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Zinc alkyl dithiophosphate	68649-42-3	0 - 2.6666
Supplier notification	Zinc alkyl dithiophosphate	68649-42-3	0 - 2.6666

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Zinc alkyl dithiophosphate; Arsenic: 1 lbs. (0.4536 kg); Cadmium: 10 lbs. (4.536 kg); lead: 10 lbs. (4.536 kg);

### State regulations

#### Massachusetts Substances

**Massachusetts RTK:** The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

#### New Jersey Hazardous Substances

**New Jersey Hazardous Substances:** The following components are listed: Zinc alkyl dithiophosphate

#### Pennsylvania RTK Hazardous Substances

**Pennsylvania RTK:** The following components are listed: Zinc alkyl dithiophosphate

**WARNING:** This product contains a chemical known to the State of California to cause cancer. Paraffin oils, ; Arsenic

**WARNING:** This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Cadmium; lead

### Inventories

**Canada inventory:** All components are listed or exempted.

**Europe inventory:** At least one component is not listed in EINECS but all such components are listed in ELINCS.

Please contact your supplier for information on the inventory status of this material.

**Australia inventory (AICS):** All components are listed or exempted.

**China inventory (IECSC):** All components are listed or exempted.

**Japan inventory (ENCS):** At least one component is not listed.

**Korea inventory (KECI):** All components are listed or exempted.

Product name	Castrol GTX High Mileage 10W-40	Product code	463542-US12, US13	Page:	5/6
Version	1	Date of issue	05/08/2007.	Format	US
				Language	ENGLISH.
			Build	5.3.1	( ENGLISH )

## 16. Other information

Label requirements           WARNING!  
 CAUSES SKIN IRRITATION.  
 MAY CAUSE EYE IRRITATION.  
 MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :           **Health**       - 1                   **National Fire**  
                                   **Flammability** 1                   **Protection**  
                                   **Physical**       0                   **Association**  
                                   **Hazard**           0                   **(U.S.A.)**  
                                   **Personal**       X  
                                   **protection**



History  
 Date of issue                05/08/2007.  
 Date of previous issue     No Previous Validation.  
 Prepared by                 Product Stewardship

**Notice to reader**

*NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.*