

# Safety Data Sheet

## STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### 1. Product And Company Identification

**Product Name:** Sub-Zero® Auto A/C Recharge Synthetic Refrigerant R-134a

**Product Number:** 345V

**Responsible Party:** STP Products Manufacturing Company  
44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810

**Information Phone Number:** +1 203-205-2900

**Emergency Phone Number:**

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)  
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for  
Outside US and Canada (call collect)

**SDS Date of Preparation:** 08/03/2018

**Product Use and Uses Advised Against:** Automotive maintenance product – For consumer and professional use

### 2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

**GHS Classification:**

<b>Physical:</b>	<b>Health:</b>
Gases Under Pressure: Compressed Gas	Simple Asphyxiant

**GHS Label Elements:**



**Warning!**

Statements of Hazard	Precautionary phrases
Contains gas under pressure; may explode if heated. Simple Asphyxiant: May displace oxygen and cause rapid suffocation.	Protect from sunlight. Do not exposure to temperatures exceeding 50°C / 122°F.

### 3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1,1,2-tetrafluoroethane	811-97-2	90-95%

The exact concentrations are a trade secret.

# Safety Data Sheet

## STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### 4. First Aid Measures

**Inhalation:** If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

**Skin Contact:** Wash exposed skin with soap and water. If skin irritation or redness develops, seek medical attention. For frostbite: warm injured area in warm (tepid) water.

**Eye Contact:** Flush eyes with large amounts of water for several minutes. If irritation or other symptoms develop, seek medical attention.

**Ingestion:** Ingestion is an unlikely route exposure for aerosol products.

**Most Important Symptoms:** May cause mild eye irritation. Direct contact with escaping gas under pressure may cause frostbite. Mists may cause mild respiratory irritation. Exposure to high concentrations can induce anesthetic effects progressing from dizziness, weakness, nausea, to unconsciousness. May cause mild skin irritation.

**Indication of Immediate Medical Attention/Special Treatment:** None known.

### 5. Firefighting Measures

**Suitable (and Unsuitable) Extinguishing Media:** Use extinguishing media suitable for surrounding fire. Cool fire exposed containers with water.

**Specific Hazards Arising from the Chemical:** Contents under pressure. Exposure of containers to heat and flames can cause them to rupture often with violent force. Burning may produce oxides of carbon and fluorine; and hydrogen fluoride.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

### 6: Accidental Release Measures

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Ventilate the area. Wear appropriate protective clothing and equipment.

**Methods and Materials for Containment and Clean-Up:** Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

**Environmental Precautions:** Report release as required by local and national regulations.

### 7. Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes and skin. Avoid breathing aerosol or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. **U.F.C. (NFPA 30B) Level 1 Aerosol.**

# Safety Data Sheet

## STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### 8. Exposure Controls / Personal Protection

#### Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
1,1,1,2-tetrafluoroethane	1000 ppm TWA AIHA WEELs

**Appropriate Engineering Controls:** General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

#### Personal Protective Equipment

**Respiratory Protection:** None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

**Gloves:** Wear impervious gloves to avoid skin contact.

**Eye Protection:** Safety glasses are recommended if eye contact is possible.

**Other Protective Equipment/Clothing:** None required.

### 9. Physical and Chemical Properties

**Appearance and Odor:** Pressurized gas and light amber liquid with ethereal odor.

<b>Physical State:</b> Gas and liquid	<b>Odor Threshold:</b> Not available
<b>pH:</b> Not determined	<b>Specific Gravity:</b> Not determined
<b>Initial Boiling Point/Range:</b> -15.2°F (-26.2°C) @ 736 mm Hg (1,1,1,2-tetrafluoroethane)	<b>Vapor Pressure:</b> 4277 mm Hg at 20°C
<b>Melting/Freezing Point:</b> -149.8°F (-101°C) (1,1,1,2-tetrafluoroethane)	<b>Vapor Density:</b> (Air = 1) 3.3
<b>Solubility In Water:</b> Water solubility: 67 mg/l at 25°C (1,1,1,2-tetrafluoroethane)	<b>Percent Volatile:</b> >90%
<b>Viscosity:</b> Not determined	<b>Evaporation Rate:</b> >1
<b>Decomposition Temperature:</b> Not available	<b>VOC Content:</b> Not determined
<b>Coefficient Of Water/Oil Distribution:</b> Not determined	<b>Autoignition Temp:</b> >662°F (>350°C) (1,1,1,2-tetrafluoroethane)
<b>Flash Point:</b> Non-Flammable	<b>Flame extension:</b> Not determined
<b>Flammability Limits:</b> LEL: Not determined UEL: Not determined	<b>Flammability (solid, gas):</b> Not applicable

### 10. Stability and Reactivity

**Reactivity:** Not normally reactive

**Chemical Stability:** Stable under normal storage and handling conditions

**Possibility of Hazardous Reactions:** Reaction with strong oxidizers may cause fire.

**Conditions to Avoid:** Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C)

**Incompatible Materials:** Strong oxidizing agents.

# Safety Data Sheet

## STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**Hazardous Decomposition Products:** Burning may produce oxides of carbon and fluorine; and hydrogen fluoride.

## 11. Toxicological Information

### Potential Health Effects:

#### **Acute Hazards:**

**Inhalation:** Mist can irritate the throat and respiratory tract. Exposure to high concentrations can induce anesthetic effects progressing from dizziness, weakness, nausea, to unconsciousness.

**Skin Contact:** May cause mild skin irritation. Contact with escaping gas under pressure may cause frostbite.

**Eye Contact:** Direct contact may cause mild eye irritation with redness, and tearing.

**Ingestion:** Ingestion is an unlikely route exposure for aerosol products. Swallowing may cause gastrointestinal disturbances.

**Chronic Effects:** None known

**Carcinogenicity Listing:** None of the other components listed at 0.1% or greater is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

### Numerical Measures of Toxicity:

1,1,1,2-tetrafluoroethane: LC50 Inhalation Rat: >500,000/4h

## 12. Ecological Information

**Ecotoxicity:** No data for product.

**Persistence and Degradability:** No data for product.

**Bioaccumulative Potential:** No data for product.

**Mobility in Soil:** No data for product.

**Other Adverse Effects:** None.

## 13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

## 14. Transport Information

**DOT Hazardous Materials Description:** UN3159, 1,1,1,2-Tetrafluoroethane, 2.2, DOT-SP 14188

**IMDG Dangerous Goods Description:** UN3159, 1,1,1,2-Tetrafluoroethane, 2.2

# Safety Data Sheet

## STP Products Manufacturing Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### 15. Regulatory Information

#### United States:

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has no RQ (reportable quantity). Oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA Hazard Category (311/312):** Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

### 16. Other Information

NFPA Rating (NFPA 704):	Health: 1	Fire: 0	Instability: 0
HMIS Rating:	Health: 1	Fire: 0	Physical Hazard: 0

REVISION DATE: 11/03/2018

REVISION SUMMARY: New SDS

PREVIOUS REVISIONS DATE: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH