

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

| | | |
|-------------------------|--|-----------------------------------|
| Ashland | Regulatory Information Number | 1-800-325-3751 |
| P.O. Box 2219 | Telephone | 614-790-3333 |
| Columbus, OH 43216 | Emergency telephone | 1-800-ASHLAND (1-800-274-5263) |
| Product name | MAXLIFE® SAE 10W-40 HIGH MILEAGE MOTOR OIL | |
| Product code | 683826 | |
| Product Use Description | No data | |

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Routes of exposure

Inhalation, Skin contact, Eye Contact, Ingestion

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing this material is not likely to be harmful.

Inhalation

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Concentration |
|--|----------------|----------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF | 64742-54-7 | >=80-<90% |

4. FIRST AID MEASURES

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

First aid is not normally required. If symptoms develop, seek medical attention.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water mist, Foam

Hazardous combustion products

carbon dioxide and carbon monoxide, various hydrocarbons, oxides of sulfur, nitrogen and phosphorus

Precautions for fire-fighting

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

**<3 % DMSO DISTILLATES
(PETROLEUM), SOLVENT-
DEWAXED HEAVY PA**

| | | | |
|-----------|-----------------------------------|-------------|---------------------|
| OSHA Z1 | Permissible exposure limit | 500 ppm | |
| OSHA Z1 | Permissible exposure limit | 2,000 mg/m3 | |
| OSHA Z1A | time weighted average | 400 ppm | |
| OSHA Z1A | time weighted average | 1,600 mg/m3 | |
| US CA OEL | Time Weighted Average (TWA) | 400 ppm | |
| | Permissible Exposure Limit (PEL): | | |
| US CA OEL | Time Weighted Average (TWA) | 1,600 mg/m3 | |
| | Permissible Exposure Limit (PEL): | | |
| ACGIH | time weighted average | 5 mg/m3 | Mist. |
| ACGIH | Short term exposure limit | 10 mg/m3 | Mist. |
| ACGIH NIC | time weighted average | 0.2 mg/m3 | Inhalable fraction. |

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826**Skin and body protection**

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state | liquid |
| Form | No data |
| Colour | No data |
| Odour | No data |
| Boiling point/boiling range | No data |
| pH | No data |
| Flash point | (>)390 °F / 199 °C, Cleveland open cup |
| Evaporation rate | No data |
| Explosion limits | 1 %(V) 6 %(V) |
| Vapour pressure | 0.01 hPa @ 70.00 °F / 21.11 °C |
| Vapour density | No data |
| Density | 0.869 g/cm3 |
| Solubility | No data |
| Partition coefficient: n-octanol/water | No data |
| log Pow | no data available |
| Autoignition temperature | No data |

10. STABILITY AND REACTIVITY**Stability**

Stable.

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

Conditions to avoid

None known.

Incompatible products

strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, various hydrocarbons, oxides of sulfur,
nitrogen and phosphorus

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

| | |
|--|----------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF | LD 50 Rat: > 15 g/kg |
|--|----------------------|

Acute inhalation toxicity

| | |
|--|-------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF | no data available |
|--|-------------------|

Acute dermal toxicity

| | |
|--|------------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF | LD 50 Rabbit: > 5 g/kg |
|--|------------------------|

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

Reportable quantity - Components

DISTILLATES (PETROLEUM), 64742-54-7 none
HYDROTREATED HEAVY PARAF

| | Health | Flammability | Reactivity | Other |
|------|--------|--------------|------------|-------|
| HMIS | 1 | 1 | 0 | |
| NFPA | 1 | 1 | 0 | |

16. OTHER INFORMATION

ASHLAND
SAFETY DATA SHEET

Page: 9

Revision Date: 11/07/2008

Print Date: 7/13/2009

MSDS Number: R0355879

Version: 1.6

MAXLIFE® SAE 10W-40 HIGH
MILEAGE MOTOR OIL
683826

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).