
CABIN AIR FILTER – INSTALLATION INSTRUCTIONS

Part No.: **CAF1746 / CAF7746** Est. Installation Time: **less than 45 min.**


Mercury Villager (1999-02); Nissan Quest (1999-02)

The cabin air filter is located under the cowl cover panel in front of the windshield, on the passenger side.


1. Lift the wiper arm away from the windshield surface until the wiper is perpendicular to the windshield. Lift and remove the wiper arm while holding the small retaining clip at the base of wiper arm outward. See ➔
2. Remove the 6 cowl cover screws. See .
3. Open the hood. Remove the 4 plastic screws from the forward edge of the cowl cover. See ➔
4. Removing Cowl Cover
5. Locate the cabin air filter on the passenger side of the vehicle by removing the four screws from the top surface of the cabin air filter top cover. Remove the cabin air filter cover.
6. Remove the cabin air filter element by pulling forward on the top surface of the filter and lifting. See below.
7. Install the new cabin air filter element into the filter retaining frame. Ensure three retaining tabs are inserted in the bottom of the filter frame.
8. Install the filter top cover and the four screws.
9. Install the cowl cover and reinstall the 4 screws anchors and the four screws.
10. Close the hood. Install the 6 screws in the cowl cover.
11. Install the windshield wiper arms.




G00214563




G00206733



G00214564



G00214567



G00214566