

Delphi Technologies



Delphi Fuel Tank Cleaning Kit

**Want your fuel pump to last?
Clean your gas tank first.**



Delphi's fuel tank cleaning kit (part number FFC01) includes:

- ✓ One bottle of low-suds cleaning solution
 - Specifically designed to easily treat and rinse up to a 40 gallon capacity fuel tank.
 - Removes microbial growth in the tank.
 - Breaks down varnish and gel from ethanol.
 - Minimizes sludge and other fuel contaminants.
 - Can extend the life of the new fuel sending unit by removing debris that may cause it harm.
- ✓ Gloves
- ✓ Lint-free cloth

Did you know?

- ✓ Most returned fuel pumps fail due to installers not cleaning the gas tank properly. Contaminants can cause wear on the impeller causing the pump to fail due to low flow/low pressure.

Before installing a new fuel pump, it's critical to properly clean the gas tank.

- ✓ Debris in your gas tank can damage your new fuel pump. And the time it takes to clean out the debris – about an hour – is nothing compared to the time it takes to redo the entire job. So save yourself time, hassle and money – clean the tank before you replace the fuel pump.
- ✓ The original fuel pump went into a clean tank. To ensure the same level of performance, the new fuel pump should go into a clean tank too.

Before You Clean (or do any repair), Think Safety First:

- Wear safety glasses and gloves.
- Store fuel in an approved container.
- Have a fire extinguisher handy.
- Clean any spills immediately.
- Always relieve fuel pressure prior to opening fuel systems.
- Never smoke or work near anything that could cause a spark or ignite fuel.
- Work in well-ventilated area with a constant flow of fresh air.
- Dispose of any product, container and cleaning residues according to all local, state and federal laws and regulations. For disposal of gasoline and any fuel-containing cleaning residues, contact your local municipality for location of the nearest appropriate waste disposal facility.

Delphi Technologies



10 Steps to properly clean the gas tank.

Clean the fuel tank during every fuel pump replacement. The original pump went into a clean tank, to ensure the same level of performance, the new pump should go into a clean tank too.

-  **1** DRAIN FUEL TANK INTO AN APPROVED CONTAINER.
-  **2** CLEAN RUST AND DEBRIS FROM THE TOP OF THE FUEL TANK
-  **3** REMOVE FUEL PUMP
-  **4** SWIRL GAS TANK. POUR OUT REMAINING GAS AND DEBRIS
-  **5** CLEAN THE TANK INTERIOR WITH A LOW-SUDS SOAP AND WATER MIXTURE *
-  **6** SWIRL CLEANING SOLUTION INSIDE TANK
-  **7** DRAIN TANK AND DRY WITH COMPRESSED AIR AND / OR A LINT-FREE CLOTH
-  **8** VISUALLY INSPECT TANK REPLACE TANK IF DAMAGED
-  **9** CONFIRM TANK IS COMPLETELY DRY (MAY TAKE APPROXIMATELY 30 MINUTES)
-  **10** RE-FILL TANK WITH FRESH FUEL

*For your convenience, we sell a Fuel Tank Cleaning Kit (FFC01).

For a video demonstration, follow the QR code, or visit our channel: [youtube.com/DelphiAutoParts](https://www.youtube.com/DelphiAutoParts)

Before you clean, think safety first:
Wear safety glasses and gloves
Have a fire extinguisher handy



delphiaftermarket.com



Delphi Technologies is a brand of BorgWarner Inc.

© BorgWarner Inc. All rights reserved. The data and illustrations are not binding. We reserve the right to modify the contents of this document on the basis of development of the products, without prior notice. | DT - 21 - 131 - E



Delphi Technologies
3000 University Drive
Auburn Hills, MI 48362 USA
For Customer Service or Technical
Hotline call 1-877-463-3574